



Manufacturer of PCB Terminal Blocks, Fuse Holders, Barrier Terminals, & Switches

## RM4U





Vital make RM4U is a screw driver operated Feed-Through terminal block. Its specially designed foot enables easy mounting and removal from the stack with a screw driver. There is a slot on the terminals to hold markers for identification. Cross connection can be achieved by shorting links. These terminals are ideal for automation, instrumentation, power and control applications.

# **PRODUCT INFORMATION:**

Product name:	RM4U
Connection method:	Feed through, screw connection type.
Rating:	32 A / 800 V / 4.0 sq mm / 0.5 Nm
HSN number:	85369090
Standard packing quantity:	100 NOS
Country of origin:	INDIA
Screw thread:	M3

### **TECHNICAL DATA:**

### **DIMENSIONS**

Height:	45.00 mm	1.77 inch	
Width:	43 mm	1.69 inch	
Thickness:	6 mm	0.23 inch	
Screw size:	М3		
Standard wire size:	4 sq mm		
Channel size:	DRC15, DRC35		

\*Continue

Off/Works: 830/2, GIDC Estate, Makarpura, Vadodara-390010

Office: +91 - 9227979802 / 4 | Sales: +91-9227979801

Email: sales@vitalelectrocomp.com | Web: www.vitalelectrocomp.com

Note: Technical specifications are subject to change without prior notice | Copyright© 2024 by Vital Electrocomp. All Rights Reserved





Manufacturer of PCB Terminal Blocks, Fuse Holders, Barrier Terminals, & Switches

## RM4U

#### **MATERIAL**

Body material:	POLYAMIDE 66	
Standard colour:	Grey	
Colour options:	Red, Yellow, Blue, Black, Green, Charcoal	

### **IEC RATING**

Connection in acc with standard	IEC 60947-7-1
Nominal Voltage	800V
Nominal current	24 A
Nominal cross section	2.5 sq mm
Short time current:	0.48 kA
Rated surge voltage:	8 kV
Degree of pollution:	3

Off/Works: 830/2, GIDC Estate, Makarpura, Vadodara- 390010

Office: +91 - 9227979802 / 4 | Sales: +91-9227979801

Email: sales@vitalelectrocomp.com | Web: www.vitalelectrocomp.com

Note: Technical specifications are subject to change without prior notice

Copyright© 2024 by Vital Electrocomp. All Rights Reserved