



TM

VITAL

Electrocomp



Google Us : Vital Connectors

Manufacturer of PCB Terminal Blocks, Fuse Holders, Barrier Terminals, & Switches


Series 45 MS

[Model : 45/2 MS, 45/3 MS]




Screw Type(Cage-Clamp Design) Connectors

45/3 MS




45/2 MS



TECHNICAL SPECIFICATIONS :

Pitch	: 5.00 mm
Nominal Rating	: 15A/300V
Dielectric Strength	: >1.5 kV
Moulded Material	: PA66 - UL94 V0 or V2
Insulation Resistance	: >1000 M Ω @ 500 Vdc
Terminal	: Tin Plated Copper Alloy
Wire Cage	: Nickel Plated Brass
Screw	: M2.5 x 0.45 mm MS Trivalent Zinc Plated
Wire Size	: 2.5 mm ²
Maximum Torque	: 0.2 - 0.25 Nm



ORDERING CODE

Series	Poles	Grade
--------	-------	-------

→ 45/2 MS ←

Number of Poles: 2 or 3

Approval Data

CE :300V / 12A / 26-14 AWG

Off/Works: 830/2, GIDC Estate, Makarpura, Vadodara- 390010

Office: +91 - 9227979802 / 4

Sales: +91-9227979801

Email: sales@vitalelectrocomp.com

Web: www.vitalelectrocomp.com

Note: Technical specifications are subject to change without prior notice

Copyright© 2024 by Vital Electrocomp. All Rights Reserved