

For datasheet check back shortly



ISO 9001:2008



Manufacturer of PCB Terminal Blocks, Fuse Holders, Barrier Terminals, & Microswitches

<p>★ Series 254</p> <p>2.54 mm 6A/63V</p>	<p>★ Series 350</p> <p>3.50 mm 10A/250V</p>	<p>★ Series 381</p> <p>3.81 mm 10A/250V</p>	<p>Series 50</p> <p>5.00 mm 15A/300V</p>	<p>Series 90</p> <p>5.00 mm 15A/300V</p>	<p>Series 45</p> <p>5.00 mm 15A/300V</p>	
<p>★ Series 58</p> <p>5.08 mm 12A/300V</p>	<p>★ Series 508</p> <p>5.08 mm 24A/300V</p>	<p>Series 58DD</p> <p>5.08 mm 12A/300V</p>	<p>Series DD</p> <p>5.08 mm 24A/300V</p>	<p>Series 5075</p> <p>7.50 mm 15A/300V</p>	<p>Series 635</p> <p>6.35 mm 24A/300V</p>	
<p>★ Series 75 / 762</p> <p>7.50 mm / 7.62mm 24A/300V</p>	<p>Series 950</p> <p>9.50 mm 10A/750V</p>	<p>★ Series 1016</p> <p>10.16 mm 50A/600V</p>	<p>VE 1008</p> <p>10A/300V</p>	<p>PFT HV 2.54 2.54 mm 4A/150V</p> <p>(H) (V)</p> <p>PFT HV 5.00 / 5.08 5.00 mm / 5.08 mm 10A/250V</p>		
<p>COM ST F</p> <p>5.08 mm 12A/250V</p>	<p>COM ST M (C)</p> <p>5.08 mm 12A/250V</p>	<p>COM 90 F</p> <p>5.08 mm 12A/250V</p>	<p>COM 90 M (C)</p> <p>5.08 mm 12A/250V</p>	<p>C381 / C350</p> <p>3.50 / 3.81 mm 10A/300V</p>	<p>C762</p> <p>7.62 mm 15A/450V</p>	
<p>PBF 1</p> <p>6.3A/250V</p>	<p>PBF 4</p> <p>6.3A/250V</p>	<p>PBF 2</p> <p>6.3A/250V</p>	<p>PBF 2M</p> <p>6.3A/250V</p>	<p>PBF 3</p> <p>6.3A/250V</p>	<p>VFC 520 10A/300V</p> <p>VFC 632 12A/300V</p> <p>HFH 1 10A/250V</p> <p>HFH 5 12A/250V</p>	
<p>Vital Microswitches (VMS) 10A/250V</p> <p>Basic Lever Roller Finger Push Thumb Push</p>						<p>30A/300V</p> <p>★ VBT 950 / VBT 825</p> <p>SWT 30A/300V</p>

★ Right Angle Option Available for all Connectors

► The recommended PCB hole diameter is 1.30 mm unless otherwise specified for that product.



Customized Color Options Available
*Subject to Minimum Quantity

830/2, GIDC Estate, Makarpura, Vadodara - 10

Tel. 9227979801 / 2 / 3

Email. info@vitalelectrocomp.com, Web. www.vitalelectrocomp.com

Google Us : Vital Connectors